

SIDEPAK™ AM510 Personal Aerosol Monitor

Intrinsically
Safe



The SIDEPAK AM510 Personal Aerosol Monitor for industrial hygiene and safety professionals displays and data logs aerosol concentration in real time. The rugged, belt-mountable laser photometer is compact and quiet, minimizing interference and worker discomfort. The built-in sampling pump lets you attach a wide variety of size-selective aerosol inlet conditioners for breathing zone or area measurements with a respirable cyclone or one of the three integrated impactors.

The SIDEPAK monitor incorporates TSI's Smart Battery Management System. This system utilizes a built-in "gas gauge" in the battery packs to monitor battery condition and provide precise run time information.

The SIDEPAK monitor's easy-to-read display shows your data as both real-time aerosol mass-concentration and 8-hour time-weighted average (TWA). The monitor's intrinsic safety rating makes it ideal for hazardous/explosive environments. With its convenient data logging and long battery life, the SIDEPAK is also ideal for extended sampling. The easy-to-use TRAKPRO™ Data Analysis Software lets you create effective graphs and reports.

User Friendly

- Small, lightweight and quiet to maximize worker acceptance
- Rugged design with secure belt clip
- Easy-to-understand user interface with only four keys
- Lockable keypad prevents tampering while sampling
- User-adjustable sample flow rate
- Define, label and store multiple calibration constants
- Easy-to-read LCD display
- Convenient, threaded tripod socket accommodates area sampling

Advanced Features

- Smart Battery Management System provides precise run time information, maximizes battery capacity and speeds charging
- Integrated pump allows use of size-selective aerosol inlet conditioners
- Built-in impactors let you choose "none," 1.0, 2.5 or 10-micron cut off
- Display shows real-time concentrations (mg/m^3) and "on-the-fly" TWA as you data log
- Display statistics: max, min and average readings, elapsed time and 8-hour TWA

Quick and Easy Reports

- Convenient preprogramming for occupational exposure sampling
- Data log for long periods and store multiple tests
- Analyze data, print graphs and create reports with TRAKPRO software
- USB port lets you conveniently connect to your computer

Power to Spare

- Long-lasting NiMH rechargeable battery packs eliminate "memory" issues
- Choice of rechargeable NiMH smart battery packs or AA-cell pack



Specifications

SidePAK AM510 Personal Aerosol Monitor

Sensitivity	
Sensor Type	90° light scattering, 670 nm laser diode
Aerosol Concentration Range	0.001 to 20 mg/m ³ (calibrated to respirable fraction of ISO 12103-1, A1 test dust)
Particle Size Range	0.1 to 10 micrometer (µm)
Minimum Resolution	0.001 mg/m ³
Zero stability	±0.001 mg/m ³ over 24 hours using 10-second time-constant
Temperature Coefficient	Approximately +0.0005 mg/m ³ per °C (for variations from temperature at which instrument was last zeroed)
Flow Rate	
Range	User-adjustable, 0.7 to 1.8 liters/min (lpm)
Temperature Range	
Operating Range	0 to 50°C (32 to 120°F)
Storage Range	-20 to 60°C (-4 to 140°F)
Time Constant (LCD display)	
Range	User-adjustable, 1 to 60 seconds
Data Logging	
Data Points	Approx. 31,000 (21 days logging once per minute)
Logging Interval	User-adjustable, 1 second to 1 hour
User-Select Calibration Factors	
Factory Setting	1.0 (non-adjustable)
User-defined Settings	3, with user-defined labels
Range	0.1 to 10.0, user-adjustable
Physical	
External Dimensions	106 mm × 92 mm × 70 mm
Dimensions	(4.2 in. × 3.7 in. × 2.8 in.) with 801724 or 801729 batteries 130 mm × 92 mm × 70 mm (5.1 in. × 3.7 in. × 2.8 in.) with 801708, 801722, 801728 or 801736 batteries
Weight	0.46 kg (16 oz) with 801724 or 801729 batteries 0.54 kg (19 oz) with 801708, 801722, 801728 or 801736 batteries
Display	2 line × 12 character LCD
Tripod Socket	1/4–20 female thread

Specifications are subject to change without notice.
Windows is a registered trademark of Microsoft Corporation.

Power Supply/Charger (P/N 2613210)

Input Voltage Range	100 to 240 VAC, 50 to 60 Hz
Output Voltage	9 VDC @ 1.0 A
Battery Charge Time	6.5 hours

Maintenance

Factory Clean/calibrate	Recommended annually
User Zero Calibration	Before each use
User Flow Calibration	As needed

Battery Information

Battery Option	Charge Time*	Intrinsically Safe
1650 mAh NiMH Pack (P/N 801724 or 801729)	3.5 hours	Yes**
2700 mAh NiMH Pack (P/N 801722 or 801728)	5.5 hours	Yes**
6-Cell AA-size Pack (P/N 801708 or 801736)	N/A	No

* Of a fully depleted battery

** All dust plugs and gaskets must be installed.

Typical Battery Life

Battery Pack	Cell Type	Hours @ 0.7 lpm	Hours @ 1.7 lpm
1650 mAh NiMH Pack (P/N 801724 or 801729)	NiMH (4.8 V, 1650 mAh) NiMH Pack	11.5	9.2
2700 mAh NiMH Pack (P/N 801722 or 801728)	NiMH (4.8 V, 2700 mAh)	19.8	15.6
6-Cell AA-size Pack (P/N 801708 or 801736) six user-supplied AA cells	AA Alkaline Cells	29.6	22.5
	AA NiMH Cells (1600 mAh per cell. Cells Can't be charged while inside AA Pack)	8.8	6.7

Communications Interface

Type	USB 1.1
Connector, Instrument	USB Mini-B (socket)

Minimum Computer Requirements for TRAKPRO Software

Communications Port	Universal Serial Bus (USB) v1.1 or higher
Operating System	Microsoft Windows® 98, Me, 2000, XP (USB not supported in Windows 95 or NT)

Approvals

Intrinsic Safety	TSI Battery Pack P/Ns: 801722, 801724, 801728 or 801729
Rating Information	INTRINSICALLY SAFE CSA Exia Class I Groups A, B, C, D T2A with 801724 or 801729 T2C with 801722 or 801728 Class II Groups E, F, G Class III File: 200507 TSI Battery Pack P/N: 801708 or 801736 NOT INTRINSICALLY SAFE



Immunity
Emissions

EN61326-1:1997 + A11998 Clause 6
EN61326:1997 + Amendment A11998



TSI Incorporated

United States: Tel: 651 490 2811 Toll Free: 1 800 874 2811 Fax: 651 490 3824 E-mail: answers@tsi.com
Germany: Tel: +49-241 523030 Fax: +49-241 523 0349 E-mail: tsigmbh@tsi.com
Sweden: Tel: +46-8-595-132 30 Fax: +46-8-595-132 39 E-mail: tsiab@tsi.com
United Kingdom: Tel: +44-1275-847837 Fax: +44-1275-842437 E-mail: tsiuk@tsi.com
China: Tel: +86-10-8260 1595 Fax: +86-10-8260 1597 E-mail: tsichina@tsi.com

or visit www.tsi.com to find your closest TSI Representative or distributor.

For current information
www.tsi.com

