



ANALYZER, CONTROLLER, TRANSMITTER

HydroACT 300



AVAILABLE SENSORS

- Free Chlorine
- Total Chlorine
- Chlorine Dioxide
- Ozone
- Dissolved Oxygen
- Suspended Solids
- pH with Temp
- ORP with Temp
- External Inputs

HIGH QUALITY - AFFORDABLE SOLUTION

Part of a range of analyzers that Chemtrac supplies, the HydroACT 300 is the entry model into the HydroACT family. The HydroACT 300 is a high quality, low cost analyzer designed to give water treatment engineers everything that they need from an analyzer and nothing that they don't. Costs are kept to a minimum by keeping digital communications, expanded analog I/O, and PID control features as options.

While the base unit HydroACT 300 comes equipped with the capability to accept one sensor (e.g. Free Cl) and provide one analog output and two relay outputs, the customer has the option of purchasing additional analog I/O and relays to expand operation up to three sensors of any type. Simply decide which measurements and features you need and the HydroACT 300 is outfitted to meet your exact needs at the best price possible. And if you are unsure what you need, a Chemtrac representative is always standing by to help you determine which features make the most sense for your application.

Customers who need an analyzer capable of accepting more than three sensors, or who require additional functionality such as datalogging, on-screen graphical reporting, or remote access via the internet should consider HydroACT 600 or HydroACT 1200 controllers.

HydroACT 300 HydroACT 600 HydroACT 1200

	HydroACT 300	HydroACT 600	HydroACT 1200
High quality sensors	•	•	•
Multilingual	•	•	•
Set up wizard	•	•	•
System logger	•	•	•
Datalogger		•	•
Event logger		•	•
PID controls	Opt	•	•
Up to 3 sensors	•	•	•
Up to 6 sensors		•	•
Up to 12 sensors			•
Analog outputs V and mA	•	•	•
Isolated universal inputs & outputs	Opt	•	•
Multi line display	•	•	•
Colored backlight	•	N/A	N/A
Color screen		•	•
Touch screen		Opt	•
Integrated modem and text alarms		Opt	Opt
Up to 4 relays	•	•	•
Up to 8 relays		•	•
Up to 16 relays			•
Remote internet access		Opt	Opt
Profibus	Opt	Opt	Opt
Modbus ASCII/RTU serial	Opt	Opt	Opt
Modbus TCP (LAN enabled)	Opt	Opt	Opt
HART	Opt	Opt	Opt
AC & DC versions	•	•	•

HydroACT 300

Chemtrac, Inc.
6991 Peachtree Industrial
Boulevard, Building 600
Norcross, GA 30092
USA

PH: 770.449.6233
US: 800.442.8722
FX: 770.447.0889
www.chemtrac.com

GENERAL SPECIFICATIONS

HydroACT 300

Power Requirement

100-240 VAC / 0.25 A or 12 VDC / 0.8 A (optional)

Languages

Any by request

Sensor Options

Free Cl, Total Cl, Cl Dioxide, Ozone, pH, ORP, Dissolved Oxygen, Suspended Solids, External Inputs

Inputs

Up to 3 configuration analog inputs; 4-20mA, 4-20mA loop-powered, 0 - 10 VDC, +/- 2000mV for pH or ISEs, PT100

2 digital inputs for signals or pulse counting

RS-485 Modbus ASCII/RTU

Outputs

Up to 3 configurable analog outputs; 4-20mA, 0-10 VDC, 0-1.25 VDC max 750 ohms impedance

Up to 4 SPST electromechanical relays rated 380 VAC, 8 A max or

Up to 4 SPST solid state relays rated 3-26 VDC, 3 A max or

Up to 2 SPST solid state relays rated 100-240 VAC, 3 A max

Alarms

2 user configurable alarms with deadband and delay for each sensor input

Communication (optional)

Allows communication/networking with PLC, SCADA, or BMS Modbus ASCII/RTU (RS485)

Profibus DP

HART

Modbus TCP (Ethernet)

Memory Backup

All user configuration is stored in non-volatile on-board flash memory

Enclosure

IP rated 65

ABS/polycarbonate/EPDM construction

Dimensions

7.6" W x 6.3" H x 4.1" D (193 mm W x 161 mm H x 103 mm D)

Weight

2.2 lbs (1 kg)

Warranty

12 months from date of purchase

