

DCX-22 Self-Contained Level Logger

Absolute Pressure and Temperature Combination Logger



Description

The DCX-22 Self-Contained Level Logger is a highly accurate, self-contained, battery powered instrument designed to record water depths and temperature over long periods. The sensor, electronics, and battery are housed in a rugged, double sealed 316 stainless steel tube for long term submersible deployment. The DCX-22 requires no external electrical wires and may be suspended with any suitable and secure cable. When it is time to download the unit's recorded data, you can simply retrieve the DCX-22 from the measurement point and remove the double sealed end cap to access the data port. The DCX-22 is available in two level ranges. When ordering, select the smallest level range that will cover the maximum expected water level change (this is not necessarily the total depth of water).

Accurate Barometric Pressure Correlation

When using the DCX-22 in shallow water depths where the influence of barometric pressure changes should be considered, we recommend that you place the DCX-22 Baro at the water surface to record the atmospheric pressure. Once the data files are downloaded to your PC, the unit's software quickly and accurately subtracts the barometric pressure values from the water pressure values. The DCX-22 Baro is built to the same high quality standards as the DCX-22 Logger.

Easy to Use Software

The DCX-22 includes simple and well structured software that is compatible with Windows™ 2000/NT/XP/ME and 9X. The software allows you to configure and read data from the DCX-22. In

particular, you can:

- Set the measuring frequency (from once per second to once every 18 hours)
- Measure data in mWC or any other unit
- Program the date and time to start measuring
- Program an event that will activate the logger
- View online data and battery condition in real time
- Export data for spreadsheet use and graphical representation

Due to the modular structure of the software, customer specific data formats can be implemented on request. In addition, a Windows™ CE-based application for accessing data on a PDA is also available upon request. Please contact Global Water to discuss these options.

Specifications

| | |
|----------------------------------|---|
| Power | Lithium battery 3.6V |
| Battery Life | 10 years @ 1 measurement per hour |
| Communications | RS-485 digital |
| Logger to PC | USB (optional RS-232) |
| Performance | Linearity: 0.05% full scale Level Accuracy: 0.1% full scale (max. 0.2% full scale) Baro Accuracy: 1mbar Long Term Stability: 0.5 mbar Overload: 2 x nominal range |
| Temperature Compensation | 14° to 104°F (-10° to 40°C) |
| Temperature Measurement Accuracy | 1°C |
| Recording Interval | 1 second to 18 hours |
| Shortest Measuring Cycle | 1x per second |
| Memory | 16,000 or 28,000 data points (depending on storage method) |
| Body Material | Stainless steel 316L (DIN 1.4435) |
| O-Ring Material | Viton® |
| Dimensions | 0.87" dia. x 9.84" long (2.2cm dia. x 28cm long) |
| Sensor Weight | 0.78 lb (355g) |
| Software Compatibility | Windows™ 2000/NT/XP/ME and 9X |

Features

- High measuring accuracy, resolution, and robustness
- Completely self-contained water level datalogger
- Rugged 316 stainless steel body with double o-ring seal
- 10 year battery life
- Up to 28,000 readings in non-volatile memory
- High data security due to the use of a non-volatile memory
- Slim 7/8 inch (22mm) diameter body
- Easy to use Windows™-based software
- Event-controlled recording and interval recording
- Record water level (pressure) and water temperature
- Software-based barometric pressure compensation with DCX-22 Baro

Ordering & Options

Level Loggers

| Order No. | Sensor Range | Price |
|-----------|----------------------|----------|
| DCX-22-2 | 0 to 66.9' (2 bar) | \$856.00 |
| DCX-22-3 | 0 to 100.37' (3 bar) | 856.00 |

Barometric Pressure Logger

| Order No. | Description | Price |
|-------------|----------------------------|----------|
| DCX-22 Baro | Barometric Pressure Logger | \$856.00 |

Data Cables*

| Order No. | Description | Price |
|-----------|----------------------------|----------|
| K-104A | USB Communication Cable | \$152.00 |
| K-103A | RS-232 Communication Cable | 114.00 |

* Note: A communication cable is required for operation. Data logging software is included.



In the U.S. call toll free at 1-800-876-1172
International: 916-638-3429
Fax: 916-638-3270
Email: globalw@globalw.com

Visit our online catalog at:
www.globalw.com
Our Address:
11390 Amalgam Way
Gold River, CA 95670