3M Personal Safety Division

3M[™] E-A-Rfit[™] Dual-Ear Validation System



3M[™] E-A-Rfit[™] Dual-Ear Validation System

The right fit test. Right now.



Features:

- Tests both ears simultaneously in under 5 seconds
- Earmuff and earplug testing capability
- Tests at 7 frequencies, from 125Hz to 8000Hz
- Science-based, objective, quantitative testing



The challenge of hearing protection.

How do you know if your workforce is protected?

Protecting workers from hazardous noise levels is an ongoing challenge for many organizations. In fact, according to the U.S. Bureau of Labor Statistics (2010)*, the most commonly recorded occupational health issue in the manufacturing sector is permanent hearing loss. The success of your safety program depends on many factors and requires more than just offering hearing protection.

Individual Fit Testing Using F-MIRE

Using F-MIRE (Field Microphone-In-Real-Ear) technology, the E-A-Rfit[™] Dual-Ear Validation System generates a Personal Attenuation Rating (PAR) in under 5 seconds for both ears, taking into account the 7 standard measured testing frequencies.

- Measures how well 3M's most popular earplugs and earmuffs perform
- Delivers a quantitative measurement of personal noise reduction for each employee
- Can help identify whether or not the employee has adequate protection

The Right Protection for Your Facility

Get results you can trust. The E-A-Rfit Dual-Ear Validation System measures the effectiveness of the hearing protection from inside the employee's ear, providing accurate, quantitative results. And because you can simultaneously test both ears, you'll have more time to educate employees on the importance of fit and compliance.



3M[™] E-A-Rfit[™] Dual-Ear Validation System

Employee-to-Employee Variability

To make sure they are getting the protection they need, you need to know the Personal Attenuation Rating (PAR) of every employee. The highest-NRR earplug or earmuff won't provide the expected protection if it doesn't fit right or isn't used right. Once you know each employee's number, you'll be on the way to yours: 100% confidence in your hearing conservation program.

Every employee is different. Every job is different. Every ear is different. Finding each employee's number will help you validate compliance and have assurance that their hearing protection is sufficient.

Program Documentation

E-A-Rfit Dual-Ear Validation System testing sessions produce a validation document that can be kept in each employee's file, providing documentation of your commitment to training and compliance with OSHA hearing conservation program guidelines.

- Features easy-to-read test results for both ears as well as testing history
- Creates digital and printable reports for both employee and company records
- Provides a direct measurement of noise reduction in decibels
- Provides an estimate of test variability

Fail.

A "fail" result means the

hearing protection is either

not fitted properly or is the

wrong type or size for the

NOTE: Finding out each employee's PAR is the first step to a successful conservation program. Once a worker's PAR is measured, you can determine if they're using the right hearing protection and ensure they're

worker's ear canal.

trained on using it properly.





Identify at-risk employees.

3M[™] E-A-Rfit[™] Dual-Ear Validation System



To learn more, visit 3M.com/EARfit. For a complete list of probed earplugs and cushions, visit EARfit.3M.com.



Distributed by: Kenelec Scientific Pty Ltd 1300 73 22 33 sales@kenelec.com.au www.kenelec.com.au © 3M 2015. All rights reserved. 3M, the color yellow for earplugs and E-A-Rfit are trademarks of 3M. Please recycle. Printed in U.S.A. 70-0716-7151-8