

FOG GENERATOR

MODEL 9308

APPLICATION NOTE 9308-001 (A4)

Fog generator model 9308 offers high output and remarkable flexibility in a compact, easy-to-transport unit. The volume control feature allows users to release the right amount of fog, ranging from small wisps to large clouds, for just about any situation. Model 9308 is controlled through a control panel that serves as either the remote or on-board control, and is connected to the machine with a standard 7-pin XLR connector.



The system uses a peristaltic pump that has a unique aluminum pump housing designed specifically for the machine. The pump, in conjunction with a steel heat exchanger, makes the equipment extremely rugged and enables it to generate higher outputs than other fog generators.

The fog fluid sits neatly encased in a well at the back of the machine. Fluid is fed to the machine via the fluid inlet that is mounted next to the well on the top of the machine. The droplet size ranges from 0.25 to 60 microns, depending on the operating flow rate. Typically, the higher the flow rate, the larger the droplet size will be.

There are a wide array of accessories which can be used with the model 9308 generator. The generator's air input can create various effects, and the machine can be cleaned quickly and easily.



TSI and TSI logo are registered trademarks of TSI Incorporated.



UNDERSTANDING, ACCELERATED

TSI Incorporated – Visit our website **www.tsi.com** for more information.

USA **Tel:** +1 800 874 2811
UK **Tel:** +44 149 4 459200
France **Tel:** +33 1 41 19 21 99
Germany **Tel:** +49 241 523030

India **Tel:** +91 80 67877200
China **Tel:** +86 10 8219 7688
Singapore **Tel:** +65 6595 6388



Distributed by:

Kenelec Scientific Pty Ltd
1300 73 22 33
sales@kenelec.com.au
www.kenelec.com.au