


AEROSOL DILUTER MODEL 3333-10

DESIGNED FOR CONTINUOUS MONITORING
OF HIGH PARTICLE CONCENTRATIONS

Monitoring ambient particle concentrations at pollution hot spots such as major traffic junctions, motorways, airports, or seaports can be challenging for Condensation Particle Counters (CPCs). The high concentrations of ultrafine particles can frequently exceed the maximum concentration limit of the CPC; this lowers the data quality, and can necessitate more frequent maintenance. The Aerosol Diluter lowers the particle concentration 10-fold by diluting the aerosol sample with a constant controlled flow of internally supplied filtered air. It is designed to enable continuous monitoring of ultrafine particle concentrations with the CPC Model 3750 or 3750-CEN.



Features and Benefits


- + Lowers the particle concentration 10-fold by diluting with a constant flow of internally supplied filtered air
- + Designed to work with flow rate of the CPC model 3750 and 3750-CEN (1.0 L/min); aerosol flow rate is provided by the attached CPC
- + Dilution air is monitored by an internal mass flowmeter and controlled by an internal blower
- + Electronic communication to CPC (Models 3750 and 3750-CEN): Diluter reads aerosol flow, maintains a fixed dilution ratio of 10:1, and communicates parameters (diluter flow, ratio, and others) to the CPC

Applications

- + Air quality monitoring of ultrafine particles
- + Environmental chamber studies
- + High particle concentration measurements in a wide variety of applications



UNDERSTANDING, ACCELERATED



SPECIFICATIONS

AEROSOL DILUTER MODEL 3333-10

Flow Specifications

Aerosol Flow Rate 1 L/min controlled by attached CPC
Dilution Ratio 10.0 +/-5%

Ambient Operating Conditions

Temperature 10 to 35 °C
Pressure 75 to 105 kPa
Humidity 0 to 90%, noncondensing

Data Acquisition

Continuous in CPC database when connected via USB with CPC 3750.
Alternative programming with 3rd party software optional.

Communication & User Interfaces

Micro-USB to connect to CPC or to computer; connection is not required to operate.

Power Requirements

100 to 240 VAC, 50/60 Hz, 200 W maximum
Auto-recovery from power outage.

Dimensions (HxWxD/Weight)

33.2 × 15.8 × 43.2 cm, 7.25 kg
13 × 6.2 × 17 in, 16 lbs
incl. inlet, outlet and feet.

Specifications reflect typical performance and are subject to change without notice.

Aerosol Instrument Manager, TSI and the TSI logo are registered trademarks, and Scanning Mobility Particle Sizer and SMPS are trademarks of TSI Incorporated.



UNDERSTANDING, ACCELERATED

TSI Incorporated - Visit our website www.tsi.com for more information.

USA Tel: +1 800 874 2811
UK Tel: +44 149 4 459200
France Tel: +33 1 41 19 21 99
Germany Tel: +49 241 523030

India Tel: +91 80 67877200
China Tel: +86 10 8219 7688
Singapore Tel: +65 6595 6388



Distributed by:
Kenelec Scientific Pty Ltd
1300 73 22 33
sales@kenelec.com.au
www.kenelec.com.au