

Temperature, Humidity, and CO₂ Smart-Sensor™

For Cobalt X™

■ Integrated triple T°, RH%, and CO₂% sensor

The smallest triple sensor designed for incubators

Dickson's triple Smart-Sensor is an innovative and convenient solution for monitoring CO₂ incubators with Cobalt X1/X2 data loggers. This compact device continually measures carbon dioxide concentration, temperature, and relative humidity inside incubators to help provide optimal control of the culture environment and notify you in case a problem arises.

Smart-Sensor electronics



l: 83 mm • Ø 12 mm
(l: 3.26 in. • Ø 0.46 in.)

Flat cable:
1 meter (39 in.)

Measurement ranges

- Temperature: 0°C to +50°C (+32°F to +122°F)
- Relative humidity: 0% to 99.9% RH
- CO₂: 0 to 20%

Applications

- In vitro fertilization (IVF) and sensitive cell cultures
- Biomedical and pharmaceutical research
- Biotechnology and life science laboratories
- Monitoring critical environmental conditions

■ Key features

- For use with OCEAView monitoring solution
- Single device measures temperature, relative humidity, and CO₂
- Small footprint fits into small incubators
- Adjustable reading frequency
- Plugs into Cobalt X1/X2 data loggers, no external power required
- Flat cable passes via incubator access port or behind door joint

■ Smart-Sensor benefits

- Calibration parameters stored directly in sensor memory
- Enables plug-and-play operation without requiring configuration
- At recalibration time, hot-swap with a freshly calibrated, ready-to-use sensor without any data gaps or down-time
- All-digital technology for maximum consistency and reliability

On-board intelligence

- Dickson's Smart-Sensor technology stores all calibration information directly in on-board memory, including calibration correction coefficients (a, a/b, or a/b/c), expanded uncertainty after calibration, drift after 1 year, sensor serial number, and calibration certificate number





Distributed by:
Kenelec Scientific Pty Ltd
1300 73 22 33
sales@kenelec.com.au
www.kenelec.com.au

DICKSON
Environmental Monitoring + Compliance Experts

Specifications

Temperature, relative humidity, and CO₂ Smart-Sensor



General	Measurement range	Expanded uncertainty	Resolution
Temperature	0°C to +50°C (+32°F to +122°F)	±0.3°C at 37°C	0.01°C
Relative humidity	0% to 99.9% RH (non-condensing)	±4%RH at 90% RH	0.05% RH
CO ₂	0 to 20% CO ₂	±0.4% at 5% CO ₂ , 37°C (+98.6°F), and 90% RH	0.1% CO ₂
Compatibility	<div></div> <div>Cobalt X2, Cobalt X1*</div> <div>* When used with Cobalt X1, only 2 sensors can be active simultaneously</div>		
Measurement environment	This sensor is only designed for incubators operating with CO ₂ injection. Multi-gas incubators (such as those with O ₂ or N ₂ injection) cannot be monitored with this sensor due to the sensor type and the presence of gases other than CO ₂ .		
Product reference	SON.CO2.0012		
Metrology			
Calibration	Calibration at 37°C (98.6°F), 5% CO ₂ and 90% RH For other options, please contact us Europe and Asia: in-house laboratory certified North America: NIST, ISO 17025 certified <i>Recalibration by sensor exchange</i>		
Details			
Sensor type	Smart-Sensor		
Material	PVC overmold and PTFE filter		
Dimensions	Sensor: length 83 mm x Ø 12 mm (length 3.26 in. x Ø 0.46 in.) Cable with Binder connector: 1 meter (39 in.)		
Electrical	Power supplied directly by Cobalt X data logger		
Protection class	IP65 (sensor unit)		

DICKSON

Environmental Monitoring + Compliance Experts

Dickson North America
Addison, IL - USA

+1 (630) 543-3747
contact@dicksondata.com

Dickson Europe
Montpellier - France

+33 (0)4 99 13 67 30
contact@dicksondata.fr

Dickson Asia
Petaling Jaya - Malaysia

+603 749 40758
contact@dicksondata.my

www.dicksondata.com

©2024 Dickson. All rights reserved. Non-contractual document.
Specifications and product photos subject to change without notice.