



® Knowledge Beyond Measure.

# Flow-focusing Monodisperse Aerosol Generator

Model 1520



**Generates highly monodisperse particles in a matter of minutes**

The FMAG can produce solid particles (0.8-8.5  $\mu\text{m}$ ) and liquid non-volatile particles (0.8-12  $\mu\text{m}$ ) from liquid solutions.

## Applications

With the ability to generate highly monodisperse particles from a wide range of materials, the FMAG is a valuable tool for numerous applications, such as:

- Generating laboratory standard aerosols for calibrating droplet and aerosol particle sizing instruments such as aerosol spectrometers and cascade impactors
- Generating known size particles at a known rate for laboratory experimentation and exposure studies
- Generating viable bioaerosols and proxy biomaterials for bioaerosol research in a variety of sectors

## Features and Benefits

- Generation of monodisperse aerosol particles of an accurately known particle diameter
- Low shear stress, non-clogging design
- Built-in corona aerosol neutralizer
- Advanced touch-screen control and user-friendly features
- Optional droplet head extension harness for remote-mounting the head upside down for large droplet production

## Compatible Materials

Using the solvent evaporation technique, a variety of solid and liquid materials can be generated by the FMAG. Successful liquid materials include oleic acid, DOP (dioctyl phthalate) and glycerol. Successful solid materials include sodium chloride, ammonium sulfate, sucrose and methylene blue. In addition to dissolved materials, suspended particles such as polystyrene latex spheres and biological microorganisms can also be generated. Recommended solvents for the FMAG include water, methanol and ethanol.



## Specifications

# Flow-focusing Monodisperse Aerosol Generator

Model 1520

### How it Works

The operation of the FMAG is based on proven aerosol generation technology and includes:

1. Stable, mechanical generation of monodisperse droplets: a liquid stream is pumped through a nozzle, and forms a narrow jet with the coaxial flow-focusing air. This jet is subjected to mechanical vibration, and breaks up into droplets that have the same volume.
2. Conditioning of droplets into particles: once generated, the droplets are dried into particles by exposure to dry dilution airflow. They are also electrically neutralized to optimize the successful transport of the particles from the generator into the intended application.

While maintaining these strengths, the FMAG also represents a significant step forward from previous technology. It incorporates:

1. Flow-focusing air. Reflected in the name 'FMAG', the use of flowfocusing air allows the instrument to operate with a much larger nozzle (100  $\mu\text{m}$ ). This significantly reduces clogging and downtime.
2. Low shear stress: the low liquid pressure operation is suitable for use with biological aerosols. Cell viability following aerosolization is enhanced when using FMAG, making it a useful tool for a wide variety of bioaerosol applications.
3. NIST-traceable particle size: The FMAG operating parameters are calibrated with NIST traceable standards. This allows users to use the FMAG for instrument calibration applications.
4. Corona aerosol neutralizer: this non-radioactive neutralizer generates a bipolar cloud of gaseous ions to neutralize any electrical charge that may be generated during the droplet and particle formation process. This feature is important in scientific research and laboratory experimentation, since unwanted or uncontrolled particle electric charge can adversely affect the behavior of aerosol particles and compromise the validity of experimental results.

### Liquid Flow Rate

1 to 24 ml/hr;  $\pm 0.50\%$

### Vibration Frequency

0 to 250 kHz;  $\pm 0.1\%$

### Droplet Diameter\*

17 to 90  $\mu\text{m}$ ;  $\pm 1.0\%^{***}$

### Particle Diameter

0.8 to 8.5 (solid) or 12 (liquid)  $\mu\text{m}^{**}$ ;  $\pm 1.0\%^{***}$

### Geometrical Standard Deviation

<1.02 for droplets; <1.05 for liquid/solid particles

### Aerosol Neutralizer

Bipolar corona (non-radioactive)

### Compressed Air Requirement

30 Std L/min; 100 to 430 kPa (14.5 to 62.5 psig); 0°C dew point

### Dimensions


273 mm x 356 mm x 483 mm (10.7" x 14" x 19") (H x D x W)

### Weight

16 kg (35 lb.)

### Power Requirements

115 or 230 VAC, 50-60 Hz, 50 W max



This product **MUST NOT** be used in residential areas or connected to low voltage from the public mains network.

Specifications are subject to change without notice.

\* Droplet diameter accuracy is based on the accuracy of the liquid flow rate and vibrating frequency

\*\* Maximum particle diameter depends on particle density. Larger particles are more difficult to be transported by the flow.

\*\*\* Particle diameter accuracy is based upon the accuracy of droplet diameter and solution concentration.

Specifications are subject to change without notice.

TSI and the TSI logo are registered trademarks in the United States and may be protected under other country's trademark registrations.



Knowledge Beyond Measure.

TSI Incorporated - Visit our website [www.tsi.com](http://www.tsi.com) for more information.

USA Tel: +1 800 874 2811

UK Tel: +44 149 4 459200

France Tel: +33 1 41 19 21 99

Germany Tel: +49 241 523030

India Tel: +91 80 67877200

China Tel: +86 10 8219 7688

Singapore Tel: +65 6595 6388

P/N 5002133 Rev C (A4)

©2025 TSI Incorporated

Printed in U.S.A.

### To Order

#### FMAG:

Specify  
1520

#### Description

Flow-Focusing Monodisperse Aerosol Generator

#### Optional Accessories

Specify

1530-98-1006

#### Description

Droplet head extension harness



Distributed by:

Kenelec Scientific Pty Ltd  
1300 73 22 33  
[sales@kenelec.com.au](mailto:sales@kenelec.com.au)  
[www.kenelec.com.au](http://www.kenelec.com.au)