



® Knowledge Beyond Measure.

High-Concentration Nanoparticle Emission Tester

Model 3795-HC



Accurate high-concentration solid particle counting in real-world emissions

Building on the proven, regulatory-compliant Nanoparticle Emission Tester (NPET 3795), the High-Concentration NPET is designed to measure total solid particle number concentrations directly from the tailpipe — whether in the field or during in-use testing.

The instrument supports a wide range of emission sources, including internal combustion engines, gasoline- and diesel-powered vehicles, and biomass power plants. Its robust, user-friendly design makes it ideal for use by researchers, regulatory inspectors, and maintenance personnel.

Equipped with a built-in catalytic stripper that removes volatile particles, the High-Concentration NPET enables accurate measurement of solid particle emissions only. Based on the same unique design principles as certification-grade instruments, it delivers laboratory-quality particle counting in real-world environments — and is capable of handling emission levels beyond certification limits, such as those upstream of after-treatment systems, upstream and downstream of Diesel or Gasoline Particle Filters, cold start emissions or biomass combustion emissions.

Features and Benefits

- Direct measurement of particle number concentration using proven Condensation Particle Counter (CPC) technology
- Sampling probe with integrated dilution to measure concentration up to 100,000,000 particles/cm³
- Selectable measurement modes:
 - Real-time data logging for research
 - User-defined protocols for reporting test cycle results

Applications

- In-use diesel machinery compliance certification
- Exhaust after treatment inspection and maintenance programs
- Diesel Particulate Filter (DPF) retrofit programs
- Gasoline Particle Filter (GPF) characterization
- Fleet emissions profiling
- DPF/GPF regeneration studies
- Cold start emission measurements
- Combustion emissions research (biomass, wood burning)



Specifications

High-Concentration Nanoparticle Emission Tester

Model 3795-HC

Differences Between the NPET Models

| | 3795 | 3795-HC |
|---------------------|--|--|
| Application | Standard tailpipe measurements or certification according to Swiss Regulation for non-road mobile machinery SR 941.242 | High concentrations such as upstream of DPF/GPF, cold start or biomass burning |
| Concentration Range | 1,000 to 5×10^6 particles/cm ³ | 2,000 to 1×10^8 particles/cm ³ |

Specifications

| | |
|------------------------------------|--|
| Particle Size Range | <50% at 23 nm >50% at 41 nm Solid particles from 23 nm to 1 μ m |
| Concentration Accuracy | $\pm 10\%$ |
| Response Time | 2.5 +/- 0.5 seconds |
| Sampling Flow | 0.7 L/min (nominal) |
| Working Fluid | 99.5%+ reagent-grade isopropyl alcohol; one charge lasts up to 4 hours |
| Catalytic Stripper | Removes >99% of volatile particles (equivalent 30 nm Count Median Diameter (CMD), Polydisperse C ₄₀ H ₈₂) |
| Environmental Operating Conditions | -10 °C to 40 °C 75 kPa to 106 kPa |
| Power Requirement | 100 to 240 VAC, 50/60 Hz, 100 W nominal, 200 W peak |
| Communications | Ethernet, 8-wire RJ-45 jack, 10/100 BASE-T, TCP/IP |
| Dimensions (H x W x D) | 10.2" x 13" x 22.4" (26 cm x 33 cm x 57 cm) |
| Weight | 13.1 kg (28.9 lbs.) |

Optional Accessories

| | |
|--------------|--|
| 3795-TAB | 10.5" Windows® tablet with Ethernet dongle and drop resistant case |
| 3795100 | Hose and probe assembly for 3795 |
| 3795-HCPROBE | Hose and probe assembly for 3795-HC |
| 803120 | Pre-soaked alcohol wicks (50 ea.) |
| 801624 | Replacement wick assembly to load wicks into NPET |
| 8016 | 30 mL isopropyl alcohol bottles (16) |



Distributed by:

Kenelec Scientific Pty Ltd
1300 73 22 33
sales@kenelec.com.au
www.kenelec.com.au



Knowledge Beyond Measure.

TSI Incorporated - Visit our website www.tsi.com for more information.

USA Tel: +1 800 874 2811
UK Tel: +44 149 4 459200
France Tel: +33 1 41 19 21 99
Germany Tel: +49 241 523030

India Tel: +91 80 67877200
China Tel: +86 10 8219 7688
Singapore Tel: +65 6595 6388

Specifications are subject to change without notice.

TSI and the TSI logo are registered trademarks of TSI Incorporated in the United States and may be protected under other country's trademark registrations.