



Features

- Easy access to configuration settings and measurement data of supported devices
- Simple setup, diagnostics, and field calibration and adjustment
- Supports Indigo-compatible measurement probes and a selection of other Vaisala devices
- Connect up to 6 devices simultaneously

Calibration is needed for verifying and maintaining measurement accuracy over time and ensuring the quality and reliability of the measurement. Vaisala Insight PC software gives quick access to the configuration and calibration of Indigo-compatible measurement probes and other supported devices.

Indigo product family

Vaisala Indigo-compatible probes are self-contained, interchangeable measurement probes. The probes can be used as standalone digital Modbus® RTU devices, or together with Indigo series transmitters or the Indigo80 indicator, which provide flexibility in terms of system interface: display, service interface, and powering options.

The Indigo product family provides various ways to interact with the device. The probe settings and calibration can be done through the local display of an Indigo transmitter or the Indigo80 indicator. Alternatively, the probes can be detached from the process and connected to a PC with a USB cable for setup and field calibration using Insight PC software.

High-quality field calibration

Field calibration is a quick way to check and validate the measurement. The simplest form of field calibration is comparison with a portable instrument.

However, when more accuracy is needed or more than one point has to be calibrated, the calibration should be made using a calibrator in the controlled environment of a laboratory or a workshop.

When a high-quality calibration in a controlled environment is needed, just detach the probe from the process, bring it to the laboratory, connect to the USB cable, and launch the Insight PC software. Up to 6 devices can be connected to Insight simultaneously. The software automatically detects the connected devices and makes calibrating easy with an intuitive graphical user interface.

Diagnostics and more

Vaisala Insight PC software provides access to diagnostics data and device specific advanced features, such as event logs, parameter backup copy, and electronic copy of the calibration certificate. It also allows easy testing and

evaluation – the 48-hour data logging functionality allows recording data from up to 6 devices simultaneously, with easy export to Excel readable format.

Technical requirements

Vaisala Insight PC software is available in English and Japanese, and it operates on Windows 10 operating systems or newer. One product specific USB cable (type A connector) per connected probe is needed.

Vaisala Insight software is available for download at vaisala.com/insight.

Devices supported by Insight software

Indigo-compatible probes

Measurement type	Probe models
Humidity and temperature	HMP1, HMP3, HMP4, HMP5, HMP7, HMP8, HMP9
Temperature	TMP1
Dew point	DMP5, DMP6, DMP7, DMP8
Carbon dioxide	GMP251, GMP252
Vaporized hydrogen peroxide	HPP271, HPP272
Moisture in oil	MMP8

Indigo transmitters and handheld devices

Device or series	Models
Indigo200 Transmitter ¹⁾	INDIGO201, INDIGO202
Indigo300 Transmitter	INDIGO300
Indigo80 Handheld Indicator	INDIGO80
DMP80 Series Handheld Dew Point Probes	DMP80A, DMP80B
HMP80 Series Handheld Humidity and Temperature Probes	HMP80L, HMP80N
GMP80P Portable Carbon Dioxide Probe with Pump Sampling	GMP80P

1) Requires model with USB-C connection, introduced in 2022. Models with WLAN connection are not supported by Insight software.

Other supported devices

Device or series	Models
DMT143 Miniature Dew Point Transmitters	DMT143, DMT143L
GMD110 Duct Carbon Dioxide Transmitter	GMD110
HMD60 Series Humidity and Temperature Transmitters	HMD62, HMD65, TMD62
HMDW110 Series Humidity and Temperature Transmitters	HMW110, HMW112, HMD110, HMD112, HMS110, HMS112, TM1110
HMM170 Humidity Measurement Module	HMM170
HMP110 Series Humidity and Temperature Probes	HMP110, HMP110T, HMP113, HMP115, HMP115T, TMP115
HMP60 Series Humidity and Temperature Probes	HMP60, HMP63
HMT370EX Series Intrinsically Safe Humidity and Temperature Transmitters	HMT370EX, HMP371, HMP373, HMP374, HMP375, HMP377, HMP378
MGP260 Series Multigas Probes	MGP261, MGP262
Polaris™ Refractometers	PR53AC, PR53AP, PR53GC, PR53GP, PR53M, PR53W, PR53SD
VDL200 Data Logger	VDL200
Ultrasonic Wind Sensor WM80	WM80



Distributed by:
Kenelec Scientific Pty Ltd
1300 73 22 33
sales@kenelec.com.au
www.kenelec.com.au

VAISALA

Published by Vaisala | B211770EN-K © Vaisala 2025

All rights reserved. Any logos and/or product names are trademarks of Vaisala or its individual partners. Any reproduction, transfer, distribution or storage of information contained in this document is strictly prohibited. All specifications – technical included – are subject to change without notice.